

Gluefast

Adhesives & Applying Equipment

The Wrinkle Tamers



COLONEL applies adhesive to back of label. Operator places label onto board stock.




Glued label board combination is fed through ADJUTANT to eliminate wrinkles.

The COLONEL Electric Label Gluer

Durable, flexible and cost-effective. The reliable Colonel produces superior results for label mounting. It applies a controlled amount of adhesive on the back of large or small labels. The glued label is then manually placed onto flat board stock, set-up boxes or any other item to be labeled. The Colonel's durable construction, with protected gear train and brass rollers, facilitates trouble-free operation. Production control is easily maintained due to a variable speed control. The thermostatically-controlled glue reservoir accommodates cold-water-based adhesives as well as hot animal glues.

The Colonel is offered in both 20" and 32" roller widths and an optional pressure-bar attachment is available for applying adhesive onto rigid/thick stock such as chipboard, plywood, corrugated, stuffed envelopes and other materials up to 5/8" thick



The ADJUTANT Label/Laminating Press

Versatile, adjustable and maintenance-free. The Adjutant label/laminating press saves labor and puts the professional, finishing touch on glued articles, whatever the material combinations. The laminating possibilities are unlimited, whether it is used in a graphic-arts or printing-house environment, or by anyone mounting large litho labels. Consistently smooth, wrinkle-free results are achieved on articles up to 1 1/8" thick in combinations of flexible/rigid, flexible/flexible and rigid/rigid materials. Paper, cloth, rubber, leather, boxboard, wood, metal and other materials are pressed quickly and easily, without special preparation.

The encased rollers and gears allow completely safe operation and make the Adjutant virtually maintenance-free. The upper rubber roller and lower metal roller apply perfect tension at all times and are completely adjustable. Variable speed control is standard.

The COLONEL Specifications

MODEL	MAXIMUM LABEL WIDTH		ROLLER SPEED ft./min.	FEED TABLE DIMENSIONS depth x width	NET WEIGHT lbs.	GLUE CAPACITY		TABLE SPACE REQUIREMENT
	inches	mm				quarts	litres	
20"	19"	483	65'-90'	10.25 x 26.25	113	3	2.8	14" x 27.5"
32"	31"	788	65'-90'	10.25 x 38"	155	5	4.7	14" x 38.5"

Standard Features:

- Double roller design for excellent glue-film control
- Variable speed control
- Thermostatically-controlled, heated glue tray

Options:

- 230-volt motor available
- 19½"-deep feed table for greater ease of operation when working with long labels
- Pressure-bar attachment for gluing materials up to 5/8" thick
- Edge/strip gluing attachment

The ADJUTANT Specifications

MODEL	MAXIMUM BOARD WIDTH ¹		ROLLER SPEED ft./min. ²	FEED TABLE DIMENSIONS	NET WEIGHT LBS.	TABLE SPACE REQUIREMENT
	inches	mm				
20"	20.75"	527	75'-103'	11.50" X 22.50"	95	17.50" x 29"
32"	32.75"	832	75'-103'	11.50" X 34.50"	117	17.50" x 41"
42"	42.75"	1086	75'-103'	11.50" X 44.50"	133	17.50" x 51"

¹Board width which is under pressure is 1½ inches less. ²Fixed speed of 85'/min only for 230 volt motors.

Standard Features:

- Rubber upper roller, metal lower roller
- Adjustable tension-and-thickness control
- Variable-speed control (110-volt motor only)

Options:

- 230-volt motor available
- Slow-speed motor for more controlled feeding